



CONFORMAT N701

DESCRIPTION: Conformat N701 is a continuous strand, glass fiber reinforcing mat. N701 is a semi-porous mat most frequently used in flat or slightly contoured parts manufactured by Compression Molding, Closed Mold Injection and Resin Transfer Molding (RTM) processes. Parts produced using N701 have excellent trimming and punchability qualities. N701 is produced with a 5 mil thick surfacing veil on both surfaces for improved surface qualities on finished parts. N701 offers excellent resistance to glass fiber movement (wash) in applications requiring high molding pressures.

BINDER SYSTEM: Can be produced with any of Superior’s binder systems.

VISUAL APPEARANCE: N701 is a light tan in color, highly consistent mat, supplied in rolls with trimmed edges. Each roll is significantly free of tears, holes, dirt, grease, foreign materials and non-uniform glass clumps or strands.

SPECIFICATIONS: Imperial

Weight per Sq. Ft. Production Range	Roll Width Production Range	Roll Length Production Range	Roll Diameter Production Range	Nominal Binder Production Range
.25 oz. Through 2 oz.	15” to 96” Per Customer Request	200’ to 900’ Based on Ounce Weight	18” to 22” Based on Ounce Weight	6% to 9% Based on Process Requirements
Tolerance (+/- 15%)	Tolerance (+/- .125”)	Tolerance (+/- 100’)	Tolerance (+/- 2”)	Tolerance (+/-2%)

SPECIFICATIONS: Metric

Weight per Sq. M. Production Range	Roll Width Production Range	Roll Length Production Range	Roll Diameter Production Range	Nominal Binder Production Range
75g Through 614g	.4m to 2.4m Per Customer Request	61m to 274m Based on Ounce Weight	46cm to 56cm Based on Ounce Weight	6% to 9% Based on Process Requirements
Tolerance (+/- 15%)	Tolerance (+/- 3.2mm)	Tolerance (+/- 31m)	Tolerance (+/- 5cm)	Tolerance (+/-2%)

*Weight per sq ft is the calculated average for each roll.

** Widths of two inch through fourteen inch available upon request with additional slitting charge.

***Binder percentage of total condensed mat before oven cure.

PACKAGING: All mats are wound onto three (3) inch I.D. (7.62cm) heavy duty cardboard cores. Each roll is individually contained within a polyethylene sleeve while on the production line, placed on a 44” (11cm)X 45”(11.25cm) X 3.5”(88mm) wooden pallet and stretch wrapped for protection during shipment. Typically there are four to six (4-6) rolls per skid. Material 36-inch (91.4cm) wide or less may be double stacked on a skid.

Optional packaging methods are available. Additional charges may apply.

- A. Four (4) inch I.D. (10.2cm) heavy duty cardboard core.
- B. Cardboard box and skid.
- C. Vacuum packaging for 10% space reduction.
- D. Cardboard box, vinyl band with stretch wrap on skid.
- E. Other methods available upon request.

Each roll is individually marked with product designation, roll number, roll width, roll length and roll weight.

STORAGE: For best performance results, it is recommended that CONFORMAT products are stored at temperatures between 10° C and 35° C at relative humidity below 85%. CONFORMAT should remain in the original packaging materials until just prior to use.

WARRANTY: See Superior’s Terms and Conditions documentation.