



Superior

COMPOSITES CO., LLC

CONFORMAT N721

DESCRIPTION: Conformat N721 is a continuous strand, glass fiber reinforcing mat. N721 is a semi-porous reinforcing mat developed specifically for pultrusion applications requiring extra pull strength and tear-out resistance while still providing good surface appearance.

BINDER SYSTEM: Superior's 176A non-soluble polyester binder.

VISUAL APPEARANCE: N721 is white to ivory in color. It is a highly consistent continuous filament glass fiber mat that is supplied in rolls with trimmed edges. Each roll is significantly free of tears, holes, dirt, grease, foreign materials and non-uniform glass clumps or strands.

SPECIFICATIONS: Imperial

Weight per Sq. Ft. Production Range	Roll Width Production Range	Roll Length Production Range	Roll Diameter Production Range	Nominal Binder Production Range
0.25 oz. Through 1.5 oz.	15" to 80" Per Customer Request	210' to 650' Based on Ounce Weight	18" to 22" Based on Ounce Weight	8% to 11% Based on Process Requirements
Tolerance (+/- 10%)	Tolerance (+/- .125")	Tolerance (+/- 50')	Tolerance (+/- 2")	Tolerance (+/- 1.5%)

SPECIFICATIONS: Metric

Weight per Sq. M. Production Range	Roll Width Production Range	Roll Length Production Range	Roll Diameter Production Range	Nominal Binder Production Range
76g Through 459g	.4m to 2.03m Per Customer Request	64m to 198m Based on Gram Weight	46cm to 56cm Based on Gram Weight	8% to 11% Based on Process Requirements
Tolerance (+/- 10%)	Tolerance (+/- 3.2mm)	Tolerance (+/- 15.2m)	Tolerance (+/- 5cm)	Tolerance (+/- 1.5%)

*Weight per sq ft is the calculated average for each roll.

** Widths of two inch (50mm) through fourteen inch (350mm) available upon request with additional slitting charge.

***Binder percentage of total condensed mat before oven cure.

PACKAGING: All mats are wound onto four (4) inch I.D. (10.2cm) heavy-duty cardboard cores. Each roll is individually contained within a polyethylene sleeve while on the production line, placed on a 44" (11cm) X 45" (11.25cm) X 3.5" (88mm) wooden pallet (Euro style as needed) and stretch wrapped for protection during shipment. Typically there are four to five (4-5) rolls per skid. Material 36-inch (91.4cm) wide or less may be double stacked on one pallet.

Optional packaging methods are available. Additional charges may apply.

- A. Three (3) inch I.D. (7.62cm) heavy duty cardboard core.
- B. Cardboard box and skid (Euro Style as needed).
- C. Cardboard box, vinyl band with stretch wrap on skid.
- D. Other methods available upon request.

Each roll is individually marked with product designation, roll number, roll width, roll length and roll weight.

STORAGE: For best performance results, it is recommended that CONFORMAT products are stored at temperatures between 10° C and 35° C at relative humidity below 85%. CONFORMAT should remain in the original packaging materials until just prior to use.

WARRANTY: See Superior's Terms and Conditions documentation.